


FINISHED Cu WEIGHT



LAYER 1 COMPONENT SIDE 1 oz.
LAYER 2 SOLDER SIDE 1 oz.

DETAIL A
LAYER STACKUP
SCALE: NONE

DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	FINISHED_SIZE	TOLERANCE_DRILL	PLATED	QTY
○	10.0	+0.0/-10.0	PLATED	1018
②	20.0	+2.0/-2.0	PLATED	37
▢2	22.0	+2.0/-2.0	PLATED	2
▢2	24.0	+2.0/-2.0	PLATED	24
③	30.0	+2.0/-2.0	PLATED	2
△	33.0	+2.0/-2.0	PLATED	4
③	36.0	+3.0/-3.0	PLATED	10
③	37.0	+3.0/-3.0	PLATED	12
③	38.0	+3.0/-3.0	PLATED	23
③	39.0	+3.0/-3.0	PLATED	18
▢2	40.0	+2.0/-2.0	PLATED	2
④	40.0	+3.0/-3.0	PLATED	31
▢4	41.0	+3.0/-3.0	PLATED	6
▢4	44.0	+3.0/-3.0	PLATED	8
◇	45.0	+3.0/-3.0	PLATED	26
④	46.0	+3.0/-3.0	PLATED	10
○	51.0	+3.0/-3.0	PLATED	1
▢5	51.0	+3.0/-3.0	PLATED	20
▢5	51.0	+4.0/-4.0	PLATED	2
▢5	52.0	+3.0/-3.0	PLATED	2
◇5	55.0	+3.0/-3.0	PLATED	9
▢6	62.0	+3.0/-3.0	PLATED	13
Ⓚ	107.0	+2.0/-2.0	NON-PLATED	3
Ⓥ	150.0	+2.0/-2.0	NON-PLATED	4

NOTES:

Via must be soldermasked.
BOARD IS D/S PTH 1.6MM THICKNESS
NO SILKSCREEN ON PADS
DRILL TOLERANCES AS PER STANDARD

